



MARINE

160A Brushless Smart Marine ESC Programmable Options

Programmable Items	Parameter Options							
	1	2	3	4	5	6	7	8
1. Running Mode	Forward Only	Forward and Reverse						
2. LiPo Cells	Auto Calc.	3S	4S	5S	6S	8S		
3. LVC Cutoff Voltage	Disabled	2.8V/cell	3.0V/cell	3.2V/cell	3.4V/cell			
4. Timing (degrees)	0.0	3.75	7.5	11.25	15.0	18.5	22.5	26.5
5. Motor Rotation	CCW	CW						

* The blacked out cells with white text are the default settings.



Firma 160 Amp Smart Brushless Marine ESC SPMXSE1160M





MARINE

160A Brushless Smart Marine ESC Specifications

SPMXSE1160M

Cont. Current	160A
Max Burst Current	1050A
LiPo Cells	3-8S LiPo
BEC Output	6V @ 8A
Size/Weight	96x91x36mm/280g

Waterproof	IP67 rated
Motor Connector	6.5mm Female Bullet
Battery Input	Dual IC5 (Series), 10 AWG 200mm
Motor Type	Sensorless Brushless
Telemetry	SRXL2 Compatible Spektrum Smart Technology



Firma 160 Amp Smart Brushless Marine ESC SPMXSE1160M

